

SERIES 2250i, 3250i, 4250i XTherm™ WINDOW

Developed and tested as Wausau INvent™ 2250i



EFCO 2250i, 3250i, and 4250i XTherm™ projected windows are designed for a wide range of applications in commercial, multi-family, education, and office buildings. This window is a flexible option in today's retrofit and new construction markets.



AAMA RATING (NAFS) AW100		STRUCTURAL LOAD (ASTM E330) 150 PSF	
AIR INFILTRATION (ASTM E283) <0.10 CFM/FT ²		WATER RESISTANCE (ASTM E547 & E331) 15 PSF	
U-FACTOR* (ANSI/NFRC 100/200) 0.34 - 0.64		CRF (AAMA 1503) 46 - 65	
STC* (ASTM E90 & E413) 31 - 42		OITC* (ASTM E90 & E413) 28 - 35	
FORCED ENTRY (ASTM F588 OR F842) GRADE 40		ACCESSIBILITY (AAMA 513) YES	

STANDARD FEATURES

- 2½", 3½" and 4½" frame depth with polyamide thermal barrier
- Flush vent construction reduces collection of dust and debris
- Dual or triple glazed option with hinged or lift-out access panels
- 5/8" or 1" between-glass Venetian blinds available
- Slide-in heavy duty steel anchors
- 1/8" principal wall thickness
- Multi-lock hardware option for improved accessibility
- Head, sill and jamb receptors available
- Broad selection of renovation panning

* Performance dependent on glass selection. Please contact your EFCO sales rep for project specific performance.