


SYSTEM 5600PG 2-1/2" CURTAIN WALL



Outside Glazed - Captured • 2-sided SSG, and 4-sided SSG
 The 5600PG is a versatile curtain wall system that can be provided in stock lengths, Pre-glaze capability for customers, and Factory fabricated/assembled & glazed. Options available for enhanced performance and fewer installation steps.



<p>STRUCTURAL LOAD (ASTM E330) VISIT EFCOCORP.COM</p> 	<p>WATER RESISTANCE (ASTM E547 & E331) 15 PSF</p> 
<p>AIR INFILTRATION (ASTM E283) 0.06 CFM/FT²</p> 	<p>CRF (AAMA 1503) CAPTURED: 57 SSG: 70</p> 
<p>U-FACTOR* (ANSI/NFRC 100/200) CAPTURED: 0.38-0.59 SSG: 0.33-0.55</p> 	<p>OITC* (ASTM E90 & E413) CAPTURED: 30</p> 
<p>STC* (ASTM E90 & E413) CAPTURED: 34</p> 	

STANDARD FEATURES

- 6", 7.5", 10" Systems
- Impact capable
- Splice sleeve doubles as lifting lug
- Pressure plate options
- Single or multi-span capability
- Sunshade, vent, and entry door capabilities
- EPDM gaskets
- Utilizes anti-buckling clips
- Factory/shop pre-glazable
- Accepts all EFCO 2.5" pressure plates and covers

* Performance dependent on glass selection. Please contact your EFCO sales rep for project specific performance.

