

SERIES 645X

5-1/2" WINDOW WALL SYSTEM



Leverage the unique characteristics of window wall for your next mid-rise or high-rise residential, mixed-use or dormitory project. EFCO's 645X window wall system is an easy-to-install solution for silicone-glazed, modern aesthetics



<p>AIR INFILTRATION (ASTM E283)</p> <p>0.06 CFM/SF</p> 	<p>STRUCTURAL LOAD (ASTM E330)</p> <p>VISIT EFCOCORP.COM</p> 
<p>U-FACTOR* (ANSI/NFRC 100/200)</p> <p>0.32 - 0.56</p> 	<p>WATER RESISTANCE (ASTM E331)</p> <p>15 PSF</p> 
<p>STC* (ASTM E90 & E413)</p> <p>33 - 36</p> 	<p>CRF (AAMA 1503)</p> <p>81 - 82</p> 
<p>OITC* (ASTM E90 & E413)</p> <p>28 - 31</p> 	

STANDARD FEATURES

- 5-1/2" frame depth
- 18mm polyamide thermal barrier
- 2-1/4" structural silicone-glazed mullions and intermediate horizontal framing members
- Easy-to-install captured head and sill "can" receptors - Flush SSG sill and jamb receptors are available.
- No exterior unit wet sealing required; pressure-equalized, rain screen design
- Zero sightline multi-lock vent inserts and integrated terrace doors
- Exterior sun shades and interior light shelves available

* Performance dependent on glass selection. Please contact your EFCO sales rep for project specific performance.