

FX32 FIXED



The series FX32 fixed window is a 3-1/4" deep system designed to meet the most stringent energy code requirements. This window can be used in schools, hospitals, government, and multi-family buildings. The system comes with a complete line of subframe, mullions, panning and trim to accommodate installation into both new and retrofit construction projects. With exceptional air infiltration and thermal performance, the FX32 is a superior solution designed to help achieve energy-savings and human comfort in today's built environment.



AAMA RATING <small>(A440)</small> AW150		STRUCTURAL LOAD <small>(ASTM E330)</small> +/- 225.6 PSF	
AIR INFILTRATION <small>(ASTM E283)</small> < 0.10 CFM/FT ²		WATER RESISTANCE <small>(ASTM E547 & E331)</small> 15 PSF	
U-FACTOR* <small>(ANSI/NFRC 100/200)</small> 0.21 - 0.53		CRF <small>(AAMA 1503)</small> 73	
STC* <small>(ASTM E90 & E413)</small> 30 - 39		OITC* <small>(ASTM E90 & E413)</small> 23 - 31	
FORCED ENTRY <small>(ASTM F588 OR F842)</small> GRADE 40		ACCESSIBILITY <small>(AAMA 513)</small> N/A	

STANDARD FEATURES

- System depth: 3-1/4"
- Nominal wall thickness: 0.080"
- Mulls to products of the same system depth
- Thermal break: Struts
- Anodized or painted finishes available
- Glass thickness range: 1" - 2"
- Panning/Trims: Available
- Subframe/Receptor system: Available
- Architecture sills: Available
- Mullions:
 - 3 Piece mullions
 - Stacking mullions

* Performance dependent on glass selection. Please contact your EFCO sales rep for project specific performance.