


# SERIES WV430 STOREFRONT



## Project-out • Casement-out

The WV430 storefront vent system is designed to be field glazed and installed with a minimal amount of labor. These vents are offered in two configurations: out-swing casements and project-out vents. Although the WV430 vent is designed to complement the flush glazed storefront, it may be glazed into any framing system with a flush surface opening and minimum frame depth of 3 1/2". The WV430 vent system is designed to incorporate many types of hardware configurations; including 4 bar hinge, multipoint locks, cam locks and roto-operators.



<b>STRUCTURAL LOAD</b> (ASTM E330) VISIT EFCOCORP.COM		<b>WATER RESISTANCE</b> (ASTM E331) 15 PSF	
<b>AIR INFILTRATION</b> (ASTM E283) <0.1 CFM/FT <sup>2</sup>		<b>CRF</b> (AAMA 1503) PO AWNING 66	
<b>U-FACTOR*</b> (ANSI/NFRC 100/200) PO AWNING 0.35 - 0.55		<b>OITC*</b> (ASTM E90 & E413) CASEMENT 26 PO AWNING 29	
<b>STC*</b> (ASTM E90 & E413) CASEMENT 33 PO AWNING 37		<b>FORCED ENTRY</b> (ASTM F588 OR F842) TYPE: B - GRADE: 40	

## STANDARD FEATURES

- Thermally broken frames
- Designed to use with storefront systems
- Spans up to 1-1/8" wide glazing pocket
- Accommodates 1/4" & 1" glazing
- Screens available
- Screen frames are extruded aluminum alloy
- Anodized and painted finishes available
- Structural silicone glazed
- Designed to incorporate many types of hardware configurations; including 4 bar hinge, multipoint locks, cam locks, and roto-operators

\* Performance based on NFRC CMAST software tool